



A KEE SAFETY PRODUCT

SAFE RAPID ACCESS

Window-Dec System



- ENGINEERED HOIST FOR LIFTING WINDOWS INTO PLACE
- INDEPENDENTLY ADJUSTABLE LEGS TO ADJUST TO UNEVEN OR SLOPING GROUND
- LONG-LIFE DURABILITY AND NON-CORROSIVE ALUMINIUM
- LIGHTWEIGHT AND COMPACT FOR EASY STORAGE AND TRANSPORTATION

Window-Dec

The **Window-Dec** has been designed to ease the installation of fitting replacement windows, by including a self locking pulley system capable of lifting up to 165lbs. It gives the installer a compliant, fully protected work platform, as well as an opening in the base of the Dec for lifting windows through. After the window passes through the hinged opening it closes to maintain the platform integrity. The Window-Dec has individually height adjustable legs, so it can adjust with uneven or sloping ground without any problems.

The Window-Dec system can be transported in either a cargo van or truck rack and can be installed with no tools required in less than 10 minutes.

After assembly and erection of the platform, the replacement window is attached to the lifting frame with the 2 straps provided and hoisted up to platform level by pulling on the rope.

Features & Benefits

- No tools required
- Quick and simple to construct
- Height adjustable in seconds
- Lightweight and compact for easy storage
- Flexibility to quickly change work locations
- Long-life durability
- Compliant with OSHA & CSA Regulations

TECHNICAL SPECIFICATION

Load rating	750lb uniformly distributed
Lifting capacity	165lb
System weight	236lb
Platform size	8.2' x 2.9' wide
Hinged opening	8' x 0.7' wide
Platform height	10' - 16'
Material	6082T6 aluminium
Deck board	WBP non-slip plywood

COMPLIANCE

ANSI A10.8-2011
CSA Z797-09
CSA Z271-10
CSA B354.5-07
OSHA 1926.451
OH&S Act and Regulations for Construction Projects
213/91



Attaching the new window

Please note: Prior to use, a full on-site risk assessment must be carried out, and in some circumstances the Window-Dec must be tied into the structure.



Method of attachment



Passing through the hinged flap



Hoisting to final position



USA
Kee Safety, Inc.
100 Stradtman Street
Buffalo, NY 14206
Tel: (716) 896 4949
Fax: (716) 896 5896
Toll Free: (800) 851 5181

www.keesafety.com
Email: info@keesafety.com

Canada
Kee Safety, Ltd.
40 North Rivermede Rd., Units 6-7
Concord, Ontario L4K 2H3
Tel: (905) 669 1494
Fax: (905) 669 4347
Toll Free: (877) 505 5003

EASI-DEC is a registered trademark of Easi-Dec Access Systems Ltd, a subsidiary of Kee Safety Group Ltd. While every effort has been made to ensure the accuracy of the information contained in this brochure Kee Safety, Inc. cannot be held responsible for any errors or omissions. Kee Safety, Inc. reserves the right to alter or withdraw products without prior notice.

Kee Safety, Inc. accepts no responsibility for any loss or damage arising from improper use of their products. ©2012 Kee Safety, Inc. All Rights Reserved.